

NE 115 NE 115B



Features :

- High-quality vocal pick up for live performance recording, and sound reinforcement applications.
- Compliments a wide variety of vocal sounds and styles with ease.
- Bottom-mounted professional XLR(Male) connector.
- Modular, lightweight design.

SPECIFICATIONS

Model No.	NE115	NE115B
Element	Back Electret-Condenser	
Polar Pattern	Unidirectional (Cardioid)	
Frequency Response	50 Hz to 16,000 Hz	
Open Circuit Sensitivity	- 62 dB± 3dB (0 dB=1V / microbar)	- 66 dB± 3dB (0 dB=1V / microbar)
Impedance	1000Ω±30%	600Ω±30%
Maximum Input Sound Level	110 dB SPL, 1 kHz at 1%T.H.D.	
Dynamic Range	80 dB, 1 kHz at Max SPL	
Signal-to-noise Ratio	64 dB , 1 kHz at 1Pa	
Battery Type	1.5V AA (UM-3)	
Battery Current	0.4 mA Typical	
Battery Life	More Than 1000 Hrs. (Fully-Charged Battery)	
Output Connector	Integral 3-pin XLRM-type	
Switch	On / Off Slide Type	
Case Material	Aluminum	
Finish	Matte-Black	
Weight	110 Grams (without Battery)	
Accessory	Stand Clamp (ABS, Black)	
Cable	5 M Two Conductor Shield Cable with Non-Balanced Ø6.3 Phone Plug	5 M Two Conductor Shield Cable with Balanced XLR Output