

NHS 717-U (with Uni-directional element)
NHS 717-N (with Noise-Cancelling element)



Features :

- Detachable headset accepting different types of gooseneck Microphone for Noise canceling or Uni-directional element.
- Comfortable wearing.

SPECIFICATIONS

Model No.	NHS 717-U	NHS 717-N
Element	Back Electret-Condenser	Back Electret-Condenser
Polar Pattern	Cardioid	Noise-Cancelling
Frequency Response	50 Hz to 18,000 Hz	50 Hz to 16,000 Hz
Open Circuit Sensitivity	- 65 dB±3dB (0 dB=1V / microbar)	- 70 dB±3dB (0 dB=1V / microbar)
Impedance	600Ω±30%	600Ω±30%
Maximum Input Sound Level	120 dB SPL, 1 kHz at 1%T.H.D.	118 dB SPL, 1 kHz at 1%T.H.D.
Dynamic Range	89 dB, 1 kHz at Max SPL	84 dB, 1 kHz at Max SPL
Signal-to-noise Ratio	63 dB , 1 kHz at 1Pa	60 dB , 1 kHz at 1Pa
Operating Voltage	1.5V~10V DC (RL = 680Ω)	
Accessory	a.Adjustable Headband b.Windscreen	