

**NPA 520S**  
**NPA 660**



NPA520S

Slide Switch

NPA660

To be supplied  
for NPA 660

**SPECIFICATIONS**

Model No.	NPA520S	NPA660
Element	Back Electret-Condenser	Back Electret-Condenser
Polar Pattern	Cardioid	Cardioid
Frequency Response	60 Hz to 17,000 Hz	20 Hz to 20,000 Hz
Open Circuit Sensitivity	- 65 dB ± 3dB (0 dB=1V / microbar)	- 65 dB ± 3dB (0 dB=1V / microbar)
Impedance	250Ω ± 30%	250Ω ± 30%
Maximum Input Sound Level	120 dB SPL, 1 kHz at 1%T.H.D.	144 dB SPL, 1 kHz at 1%T.H.D.
Dynamic Range	91 dB, 1 kHz at Max SPL	116 dB, 1 kHz at Max SPL
Signal-to-noise Ratio	65 dB, 1 kHz at 1Pa	66 dB, 1 kHz at 1Pa
Operating Voltage	Phantom Power 9-52 V DC, 2mA typical Battery 1.5V (AAx1)	Phantom Power 9-52 V DC, 2mA typical
Weight	180g	273g
Dimensions	Ø22X516mm	Ø24X565mm
Output Connector	Integral 3-pin XLRM-type	Integral 3-pin XLRM-type