

NPM 110
NPM 130



NPM110



NPM130



- NPM110A (With Detachable Phantom Power Adapter NPTS10)
- NPM110B (With Integrated Phantom Power Adapter NPTS10)
- NPM110C (With Detachable Phantom Power Adapter NPTS11)
- NPM110D (With Detachable Phantom / Battery Power Adapter NPTS42)

- NPM130A (With Detachable Phantom Power Adapter NPTS10)
- NPM130B (With Integrated Phantom Power Adapter NPTS10)
- NPM130C (With Detachable Phantom Power Adapter NPTS11)
- NPM130D (With Detachable Phantom / Battery Power Adapter NPTS42)

SPECIFICATIONS

Model No.	NPM110	NPM130
Element	Back Electret-Condenser	
Polar Pattern	Cardioid	
Frequency Response	20 Hz to 20,000 Hz	50 Hz to 18,000 Hz
Open Circuit Sensitivity	- 65 dB± 3dB (0 dB=1V / microbar)	- 65 dB± 3dB (0 dB=1V / microbar)
Impedance	250Ω±30%	200Ω±30%
Maximum Input Sound Level	145 dB SPL, 1 kHz at 1%T.H.D.	145 dB SPL, 1 kHz at 1%T.H.D.
Dynamic Range	118 dB, 1 kHz at Max SPL	116 dB, 1 kHz at Max SPL
Signal-to-noise Ratio	67 dB , 1 kHz at 1Pa	65 dB , 1 kHz at 1Pa
Operating Voltage	Phantom Power 9-52 V DC, 2mA typical	
Dimensions	Ø6(Gooseneck) X140 mm(Overall Height)	
Output Connector	Integral 3-pin XLRM-type	