

NPS 320
NPS 322



NPS322



- NPS 322PB (WITH PHONE PLUG LEAD, COLOR : BLACK)
- NPS 322PW (WITH PHONE PLUG LEAD, COLOR : WHITE)
- NPS 322XB (WITH XLR 3PIN MALE LEAD, COLOR : BLACK)
- NPS 322XW (WITH XLR 3PIN MALE LEAD, COLOR : WHITE)



NPS320

- NPS 320A (With Detachable Phantom Power Adapter NPTS10)
- NPS 320B (With Integrated Phantom Power Adapter NPTS10)
- NPS 320C (With Detachable Phantom Power Adapter NPTS11)
- NPS 320D (With Detachable Phantom / Battery Power Adapter NPTS42)

SPECIFICATIONS

Model No.	NPS320	NPS322
Element	Back Electret-Condenser	
Polar Pattern	Cardioid	
Frequency Response	50 Hz to 18,000 Hz	
Open Circuit Sensitivity	- 65 dB± 3dB (0 dB=1V / microbar)	- 63 dB± 3dB (0 dB=1V / microbar)
Impedance	200Ω±30%	1000Ω±30%
Maximum Input Sound Level	145 dB SPL, 1 kHz at 1%T.H.D.	120 dB SPL, 1 kHz at 1%T.H.D.
Dynamic Range	116 dB, 1 kHz at Max SPL	90 dB, 1 kHz at Max SPL
Signal-to-noise Ratio	65 dB , 1 kHz at 1Pa	64 dB , 1 kHz at 1Pa
Operating Voltage	Phantom Power 9-52 V DC, 2mA typical	Battery 1.5V
Dimensions	80 X65X19 mm	90 X115X17 mm
Output Connector	Integral 3-pinTB3M	
Material of Housing	Zinc Die-Cast	