

NPTS 20
NPTS 50
NPTS 52



NPTS20

SPECIFICATIONS

NPTS 20

- For gooseneck microphone with XLR/male connector
- Anti-Shock mounting
- Built-in push to lock switch
- Cannon XLR 3P/female input connector and cannon XLR 3P/male output connector
- Stylish design
- Dimensions : 160mm(L) × 124mm(W) × 50mm(H)
- Weight : 1.3Kg
- MATERIAL OF BASE : Zinc Die-Cast



NPTS50

NPTS 50

- For gooseneck microphone with XLR/male connector
- Anti-Shock mounting
- Cannon XLR 3P/female input connector and cannon XLR 3P/male output connector
- Stylish design
- Dimensions : 120mm(L) × 125 mm(W) × 40mm(H)
- Weight : 1.2 Kg
- MATERIAL OF BASE : Zinc Die-Cast



NPTS52

NPTS 52

- For gooseneck microphone with XLR/male connector
- Anti-Shock mounting
- Built-in push to lock switch
- Cannon XLR 3P/female input connector and cannon XLR 3P/male output connector
- Stylish design
- Dimensions : 120 mm(L) × 125mm(W) × 40 mm(H)
- Weight : 1.2 Kg
- MATERIAL OF BASE : Zinc Die-Cast