

NPTS 54

NPTS 56 (PTT/PTL Selectable)



NPTS54

SPECIFICATIONS

NPTS54

- For Gooseneck Microphone with XLR / Male Connector
- Anti-Shock Mounting
- On-Off (Push to Lock) Switch with LED Indicator
- OPERATING VOLTAGE : Phantom Power 48V~52V DC
- Cannon XLR 3P/Female Input Connector and Cannon XLR 3P/Male Output Connector
- Stylish Design
- DIMENSIONS : 120 mm(L) × 125 mm(W) × 40 mm(H)
- WEIGHT : 1.2 Kg
- MATERIL OF BASE : Zinc Die-Cast

NPTS56

- For Gooseneck Microphone with XLR / Male Connector
- Anti-Shock Mounting
- Built-in Push to Lock and Push to Talk Selection Switch with LED Indicator
- OPERATING VOLTAGE : Phantom Power 48V ~ 52V DC
- Cannon XLR 3P/Female Input Connector and Cannon XLR 3P/Male Output Connector
- Stylish Design
- DIMENSIONS : 120 mm(L)×125 mm(W)×40 mm(H)
- WEIGHT : 1.2 Kg
- MATERIL OF BASE : Zinc Die-Cast



NPTS56

NPTS54 WITHOUT SWITCH
NPTS56 WITH SWITCH